

FASTRACK

Fastrack is a premier, multi-layer sports surface that provides high performance and superior durability. Fastrack features a 2.5mm performance rubber surface bonded to a 12mm recycled rubber underlayment. This floor is available in 13 color patterns.



PRODUCT FEATURES

- Sound and shock absorbent
- Fade resistant/wears well
- Slip resistant wet or dry
- Spike resistant
- Indoor Only

APPLICATIONS

- Multi-purpose areas
- Indoor tracks
- Gymnasiums
- Aerobic centers

PRODUCTION OPTIONS

Rolls: 14.5mm (2.5mm+12mm) x 48" (1.2m)

Interlocking Tiles: 14.5mm (2.5mm+12mm) x 23" (58cm) x 23" (58cm)

PHYSICAL DATA

PERFORMANCE CRITERIA DENSITY

Tensile Strength
Flexibility ¼" mandrel
Thermal Conductivity
Static Load Limit
Coefficient of Friction
V.O.C. Compliant
Abrasion Resistance
Pill Test
Vertical Deflection / Deformation
Surface Effect Slip Resistance
Ball Rebound
Force Reduction

TEST METHOD

ASTM D 412
ASTM F 137
ASTM C 518
ASTM F 970 @ 250PSI
ASTM D 2047
ASTM D 5116
ASTM D 3389 / EN 649
ASTM D 2859
ASTM F 2772
ASTM F 2772
ASTM F 2772
ASTM F 2772

RESULTS

>200 PSI
Pass
>0.4"
0.009" Typical
>0.9
Yes
<1g, 100 cycle
Pass
2.66mm
Pass
98.8%
35.7%