

FASTRACK

Fastrack is a premier, multi-layer sports surface that provides high performance and superior durability. Fastrack features a 2.5mm composition rubber surface fusion bonded to a 12mm composition rubber backing.



PRODUCT FEATURES

- Sound and shock absorbent
- Fade resistant/wears well
- Slip resistant wet or dry
- Spike resistant
- Indoor Only

PRODUCT OPTIONS

Rolls:

14.5mm (2.5mm+12mm) x 48" (1.2m)

7.5mm (2.5mm + 5mm)x 48" (1.2m)

Interlocking Tiles:

14.5mm (2.5mm+12mm) x 23" (58cm) x 23" (58cm)

PHYSICAL DATA

Performance Criteria Density

Tensile Strength
Flexibility 1/4" mandrel
Thermal Conductivity
Static Load Limit
Coefficient of Friction
V.O.C. Compliant
Abrasion Resistance
Pill Test
Vertical Deflection / Deformation
Surface Effect Slip Resistance
Ball Rebound
Force Reduction

Test Method

ASTM D 412
ASTM F 137
ASTM C 518
ASTM F 970 @ 250PSI
ASTM D 2047
ASTM D 5116
ASTM D 3389 / EN 649
ASTM D 2859
ASTM F 2772
ASTM F 2772
ASTM F 2772
ASTM F 2772

Results

>200 PSI
Pass
>0.4"
0.009" Typical
>0.9
Yes
<1g, 100 cycle
Pass
2.66mm
Pass
98.8%
35.7%